



Communications

# CALLBOX

- 免月租費免通話費,直接語音通話.
- 安裝方便, 免去麻煩的拉線.
- 可搭配太陽能電池系統,方便偏遠地方無電源時使用.
- 可搭配移動式手持裝置,隨時掌控狀況.
- 不銹鋼外殼堅固耐用.
- 可搭配不斷電系統.
- 具有RADIO CHECK跟廣播功能.



- 公司收貨區(案例):  
當貨車來到公司收料區時,送貨人員利用無線呼叫鈴,通知到處跑來跑去的收料員(配帶迷你無線電對講機),收料員回覆立即出去收料,如此有效率完成通知方式(一般門鈴是無法達到),這樣產品是不是您想要的?



- 在地服務,迅速維修,一年保固,永久服務
- 立即使用看看,請撥打客服專線

電話: 04-22651199

網址: <http://www.shco.com.tw/>



## General

Frequency Range	VHF:144~146MHz / UHF:430~432MHz
Channel Number	512
Current Drain	TX $\leq$ 6.5 A RX $\leq$ 0.8A
Operating Voltage	13.8V $\pm$ 15%
Operation mode	F3E (FM)
Frequency Stability	$\pm$ 2.5ppm
Operating Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C
Antenna Impedance	50 $\Omega$
Dimension(HxWxD)	Microphone:110x30x14.3m/m Body:65x38x106m/m
Weight	800g

## Transmitter

Output Power	<25W / <15W / <5W
Spurious emission	70dB
Maximum frequency deviation	Wide : $\pm$ 5kHz / Narrow : $\pm$ 2.5kHz
Noise and hum ratio	Wide : 40dB / Narrow : 36dB
Microphone Impedance	1K $\Omega$

## Receiver

Sensitivity (12dB SINAD)	Wide : 0.2 $\mu$ V / Narrow : 0.25 $\mu$ V
Adjacent Channel Selectivity	Wide : 70dB / Narrow : 60dB
Intermodulation rejection ratio	60dB
Audio Output Power	>500mW
Audio Distortion	$\leq$ 10%
Audio Output Impedance	16 $\Omega$